

**MACHINE SPECIFICATIONS**
**KITAKO**
**VT-4 Series**

	<b>VT4-200</b>	<b>VT4-350</b>	<b>VT4-550</b>
<b>Max. turning</b> (dia. × L)	∅ 200mm × 200mmL	∅ 350mm × 200mmL	∅ 550mm × 305mmL
<b>Spindle nose</b>	ASA A <sup>2</sup> -6	ASA A <sup>2</sup> -8	ASA A <sup>2</sup> -8
<b>Spindle speeds</b>	A:30 to 3,000 rpm; B:40 to 4,000 rpm	A:25 to 2,500 rpm.; B:32 to 3,200 rpm	15 to 1,500 rpm
<b>X-axis travel</b>	170mm (6.69in.)	300mm (11.81in.)	450mm (17.72in.)
<b>Z-axis travel</b>	350mm (13.78in.)	450mm (17.72in.)	650mm (25.59in.)
<b>Rapid traverse</b> (X/Z)	8,000/12,000 mm/min.	20,000/20,000mm/min.	4,000/8,000mm/min.
<b>Turret</b>	6st. drum × 2		
<b>Mass of machine</b>	8,000kg	12,000kg	22,000kg
<b>Power source</b>	60KVA	86kVA	100kVA